

Rec 10/13/86

LIST

MATERIAL SAFETY DATA SHEET

USG INDUSTRIES, INC.
101 S. Wacker Drive, Chicago, IL 60606

Day 312/321-4383
Night 312/321-4382

SECTION I

Tile Adhesive - Vinyl Asbestos
CMC-376

PRODUCT NO: 15038

PRODUCT: CMC 376 Clear Vinyl Asbestos Tile Adhesive
DATE ISSUED: November 14, 1983
CHEMICAL FAMILY: Synthetic Latex - Resin Emulsion

SECTION II
HAZARDOUS INGREDIENTS

MATERIAL:	%	TLV:
Mineral Spirits	4-6	200 PPM

SECTION III
PHYSICAL DATA

SPECIFIC GRAVITY (H2O = 1): 1.0
APPEARANCE AND ODOR: Off white soft paste, mild odor.

SECTION IV
FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED): 102 F (PMCC)
EXTINGUISHING MEDIA: Will not support combustion. Will not propagate flame.
SPECIAL FIRE FIGHTING PROCEDURES: None
UNUSUAL FIRE AND EXPLOSION HAZARDS: None

SECTION V
HEALTH HAZARD DATA

EFFECTS OF OVEREXPOSURE: May cause eye irritation. Inhalation may cause headache, nausea, and dizziness.
EMERGENCY AND FIRST AID PROCEDURES:
EYES: Flush with water for 15 minutes. If irritation continues, see physician.
SKIN: Wash with mild soap and water.
INHALATION: Remove from exposure. Call physician.
INGESTION: DO NOT induce vomiting. Call physician.

PRODUCT NO: 15038

Page: 2

PRODUCT: CMC 376 Clear Vinyl Asbestos Tile Adhesive

SECTION VI REACTIVITY DATA

STABILITY: Stable

HAZARDOUS POLYMERIZATION: Will not occur.

SECTION VII SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

Scrape up and place contents in closed container.

WASTE DISPOSAL METHOD: In accordance with local, state and federal regulations.

SECTION VIII SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION: NIOSH approved organic vapor respirator if above TLV.

VENTILATION: Local if above TLV.

PROTECTIVE EQUIPMENT: Safety glasses and polyethylene gloves recommended.

SECTION IX SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in a cool place with adequate ventilation. Avoid prolonged or repeated contact with skin.